



CERTIFICATION RECORD

The company named below has been authorized by CSA International to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 065927_0_000
Class No: 6225 01 FUSEHOLDER ASSEMBLIES

SUBMITTOR

4552812 Sato Parts Co., Ltd.
3F Sanyu Bldg
3-42-1 Hongo
Bunkyo-ku, Tokyo 113-0033
Japan

FACTORIES

4552815 Sato Parts Co., Ltd.
Niigata Factory
2255-2 Torigoe
Nagaoka - shi
Niigata - ken, Niigata 940-2316
Japan

January 29, 2009(Replaces:September 8, 2004)

Extractor type fuseholders, intended for through-the-panel mounting:

- Cat No F-70, 30A and less, 250V ac and less, for use with 6.35mm by 31.8mm cartridge fuses.
- Cat No F-75, 10A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
- Cat No F-85, 10A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Type F-120, 10A and less, 250V ac and less, for use with 6.4 by 30mm or 6.35 by 31.8mm cartridge fuses.
- Type F-130, 10A and less, 250V ac and less, for use with 6.4 by 30mm or 6.35 by 31.8mm cartridge fuses.
- Type F-140, 10A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
- Type F-150, 10A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Cat Series F-220 with suffixes, 16A and less, 250V ac and less, for use with 5.2 by 20mm, 6.4 by 30mm and 6.35 by 31.8mm cartridge fuses.
- Cat No F-240, 10A and less, 250V ac and less, for use with 6.4 by 30mm or 6.35 by 31.8mm cartridge fuses.

Extractor type fuseholders, intended for printed circuit board mounting:

- Cat No F-33S, 6A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.

- Cat No F-33L, 8A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
- Cat Nos F-100, F-105, 10A and less, 250V ac and less, for use with 5.2mm by 20mm cartridge fuses.
 - Cat No F-110, 10A and less, 250V ac and less, for use with 6.4mm by 30mm or 6.35 mm by 31.8 mm cartridge fuses.
 - Cat Series F-230 with suffixes, 16A and less, 250V ac and less, for use with 5.2 by 20mm, 6.4 by 30mm and 6.35 by 31.8mm cartridge fuses. Open type fuseholders, single pole:
 - Cat No F-60, 5A and less, 125V ac and less for use with 5.2mm by 20mm cartridge fuses.
 - Cat No F-61, 10A and less, 250V ac and less for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
 - Cat No F-64, 10A and less, 250V ac and less for use with 5.2mm by 20mm cartridge fuses.
 - Cat No F-65, 10A and less, 250V ac and less for use with 6.4mm by 30mm or 6.35mm by 31.8mm cartridge fuses.
 - Cat No F-66, 20A and less, 250V ac and less for use with 10.31mm by 38.1mm cartridge fuses.
 - Type F-200, 10A and less, 250V ac and less, for use with 6.35 by 31.8mm or 6.4 by 30.0mm cartridge fuses. Open type fuseholders, 1 and 2-pole:
 - Type F-180, 10A and less, 250V ac and less, for use with 6.35 by 31.8mm or 6.4 by 30.0mm cartridge fuses. Note: These fuseholders are Certified as components for use only in other Certified equipment where the suitability of the combination is determined by the Canadian Standards Association.
 - Fuseholders for cartridge ferrule fuses, suitable for PWB mounting, 1-pole, 2-pole, or 3-pole, model series F-300, rated 250 V, 5A. Note: These fuseholders are supplied only to manufacturers, as components, for the assembly of certified electrical equipment and the suitability of the combination will be determined on the final product.
- Fuseholders, extractor type, intended for panel mounting, Model F-250, rated 250 V ac, 20 A.

Note: These fuseholders are certified as components for use in the assembly of certified electrical equipment and the suitability of the combination will be determined on the final product.

- Fuseholders for cartridge ferrule fuses, dimensions of 6.35 diameter by 31.8 mm long or 6.4 diameter by 30.0 mm long fuses, suitable for PWB mounting, 1-pole or 2-pole, Model Series F-350, rated 250 V, 10 A.

Note: These fuseholders are supplied only to manufacturers, as components, for the assembly of certified electrical equipment and the suitability of the combination will be determined on the final product.